


HDPE FLAP VALVE, FLANGE CONNECTION 10° ANGLE, Ø100 - Ø2000 MM. ATK-F**SKU:** 670ATK-F**ADDITIONAL INFORMATION**

Diameter Ø 100, 125, 150, 200, 250, 300,
400, 500, 600, 700, 800, 900,
1000, 1100, 1200, 1400, 1500,
1600, 1800, 2000

Flange mounted HDPE Flap Valve ATK-F.
Opening Ø100 mm - Ø2000 mm. 5 M.w.c. On seating.

This HDPE non-return valve is mostly installed partly or completely submerged (in surface water / sewage / in case of emergency / flood protection), regulating a water flow in a single direction and preventing any back flow. To be applied practically in all kinds of environments with free flow / gravitation.

The flap valve is hung at a 10 degree angle to ensure a water tight seal. This version is suitable for flange mounting. Standard PN10 drillings. Other drillings on request.

Standard water pressure will be 1 M.w.c. from top of culvert on seating long duration (50 years).
5 M.w.c. from invert level on seating short duration (72 hours)

Freedrain flap valves with stainless steel hinge pins are equipped with HDPE ribs. Bigger dimensions shall be reinforced with stainless steel U-profiles. They can also be manufactured in a custom made size or shape (square /rectangular), or designed to suit other operating water pressures.

Materials used:

- HDPE
- SS316L

-EPDM sealing

Advantages of the Freedrain flap valve:

- Design life of 50 years
 - First class materials used
 - Maintenance free
 - Fast opening moment, so no accumulation of dirt in the pipe
 - Light weight and easy handling.
 - Easy to adjust design for custom made requirements.
 - High UV protection
 - Easy replaceable Lip seal
-

VARIATIONS

Image	SKU	Description	Diameter Ø
	670ATK0250F		250
	670ATK0200F		200





Image	SKU	Description	Diameter Ø
	670ATK0150F		150
	670ATK0125F		125
	670ATK0100F		100
	670ATK0300F		300





Image	SKU	Description	Diameter Ø
	670ATK0400F		400
	670ATK1300F		500
	670ATK0600BS-1		600
	670ATK0700BS-1		700





Image	SKU	Description	Diameter Ø
	670ATK0800F		800
	670ATK0900F		900
	670ATK1000F		1000
	670ATK1100F		1100










Image	SKU	Description	Diameter Ø
 A square concrete plate with a black metal grate and a central circular opening.	670ATK1200F		1200
 A square concrete plate with a black metal grate and a central circular opening.	670ATK1400F		1400
 A square concrete plate with a black metal grate and a central circular opening.	670ATK1500F		1500
 A square concrete plate with a black metal grate and a central circular opening.	670ATK1600F		1600

Image	SKU	Description	Diameter Ø
	670ATK0500F		1800
	670ATK2000F		2000
			
			
			



PRODUCT DESCRIPTION

Flange mounted HDPE Flap Valve Type ATK-F

[Download product sheet](#)

Type	ATK-F
Material flape valve door	HDPE, High Density Polyethylene
Material frame plate	HDPE, High Density Polyethylene
Material Hinges	Stainless steel 316L 1.4404
Material Sealing flap valve door	EPDM, Ethylene Propylene Diene Monomer
Material Sealing frame plate	Neoprene
Material ballastweight	Stainless steel 316L 1.4404
MWC	1-5 mwc
Opening	Ø 100 - Ø 2000 mm.
Options	Other flange drillings on request

Modifications and errors reserved.

ADDITIONAL INFORMATION

Diameter Ø 100, 125, 150, 200, 250, 300, 400, 500, 600, 700, 800, 900, 1000, 1100, 1200, 1400, 1500, 1600, 1800, 2000

