


**PENSTOCK, 5MWC, FLANGE CONNECTION, TYPE ASG-F****SKU:** 670ASG-F**ADDITIONAL INFORMATION**

**Diameter Ø** 100, 125, 150, 200, 250, 300,  
400, 500, 600, 700, 800, 900,  
1000, 1100, 1200, 1400, 1500

The Freedrain penstocks are used in surface water, sewerage systems, (sewerage) water treatment systems etc. to (temporarily) block or allow to pass water

They are manufactured from high quality HDPE and they will be reinforced with Stainless Steel 316L profiles. HDPE is lightweight and has a high chemical resistance. Standard, the penstocks are fitted with a SS316L non-rising spindle

**This version is suitable for flange mounting. Standard PN10 drillings. Other drillings on request.**

The penstock contains a vertically moving door which can block the water supply on both sides. Tightening shall be effected by means of a special EPDM flat/lip shaped rubber profile to withstand 5 meter water column pressure on both sides, without any visible deformation.

Materials used:

-HDPE

-SS316L

-EPDM sealing

Advantages of the Freedrain penstocks:

- Design life of 50 years.
- First class materials used.
- Less maintenance.
- Light weight and easy handling.
- Easy to adjust the design for custom made requirements.
- High UV protection.
- Easy replaceable Lip seal.

Other options:

- Rising spindle situation.
  - Several manual and electrical operations.
  - Heavy duty penstocks with higher water pressure .
  - Square, rectangular or egg-shaped openings.
  - Weir penstock with downwards opening
- 

## VARIATIONS





Image	SKU	Description	Diameter Ø
	ASG0100F		100
	ASG0125F		125
	ASG0150F		150
	ASG0200F		200





Image	SKU	Description	Diameter Ø
	ASG0250F		250
	ASG0300F		300
	ASG0400F		400
	ASG0500F		500







Image	SKU	Description	Diameter Ø
	ASG0600F		600
	ASG0700F		700
	ASG0800F		800
	ASG0900F		900

Image	SKU	Description	Diameter Ø
	ASG1000F		1000
	ASG1100G-1		1100
	ASG1200G-1		1200
	ASG1400G-1		1400

**Image**

**SKU**

**Description**


**Diameter Ø**



ASG1500G-1

1500







## PRODUCT DESCRIPTION

Penstock TYPE ASG-F with standard PN10 flange.

[Download product sheet](#)

Type	ASG-F
Material Bridge	Stainless steel 316L 1.4404
Material Guides	Stainless steel 316L 1.4404
Material Frame Plate	HDPE
Material Reinforcement Profiles	Stainless steel 316L 1.4404
Material Spindle	Stainless steel 316L 1.4404
Material Spindle Nut	Bronze
Material Sealing Door / Frame Plate	Neoprene
Material Sealing Penstock / Concrete	EPDM
Material Operation Point	Stainless steel 316L 1.4404
Material Spindle Stop	Stainless steel 316L 1.4404
Material Bare Shaft	POM

## ADDITIONAL INFORMATION

**Diameter Ø** 100, 125, 150, 200, 250, 300, 400, 500, 600, 700, 800, 900, 1000, 1100, 1200, 1400, 1500

